

Scale up the possibilities with the new HP-5000




progilitytech.com

Innovative | Flexible | Responsive | Customer focused

Scale up the possibilities with the new HP-5000

Designed to adapt to your growing business needs, the new **HP-5000** is a effective and dynamic soft witch offering industry standard redundancy and resiliency on every front. With complete adaptibility, state of the art build and cost effective operations, the HP-5000 offers you complete technical flexibility with Analog & SIP extensions.



- Industry standard Server based solution
- IP @ core
- Operating system CentOS 6.8 Linux
- Hot standby functionality
- Highly scalable, up-to 5000 Analog / SIP extensions
- Modular high density gateway to support Analog extensions
- 128 Analog extensions in 1U size gateway
- Multiple choices for PSTN gateways
- Built in Voicemail with Unified Messaging and Voice Recording
- Built in Interactive Voice Response System
- PC based Operator Console
- Point to point Video call support using H.261, H.263, H.263+, H.264, VP8, Vp9

The HP-5000 is the optimal solution to your needs providing robust enterprise communication possibilities, advanced tools and complete customizations to your business operations.

HP-5000 Variants


HP-5000 is available in 3 different variants depending upon the customer requirement.

HP-5000 Variant	Small	Medium	Large
Maximum Number of Subscribers	500	2,000	5,000
Hot Stand by Redundancy	Yes	Yes	Yes
Maximum number of PRI ports (1 port = 30 Channels)	16	16	16
Maximum Number of VoIP Trunk Channel	500	2,000	5,000
Maximum Number of Voice Mail users	500	2,000	5,000
Maximum Number of Voice Recording users	500	2,000	5,000
T.38/T.30 Fax support	Yes	Yes	Yes

Typical Deployment Scenarios


HP-5000 supports Server-Gateway architecture. Typical deployment scenarios of HP-5000 can be seen as below.

a. Stand-alone architecture



In a stand-alone architecture it would be single node system. HP-5000 could be deployed as Simplex or as a Duplex in a hot standby mode.

b. Distributed architecture




Distributed architecture helps enterprise customers to connect flawlessly who have geographically separated offices distributed over IP infrastructure.

Analog Extension Gateway

 HP-5000 supports Analog extensions via Analog gateways (FXS) called as HP-GW

series. It's a cost-effective SIP based Analog (FXS) gateway offering high-quality Voice, Fax and Modem over IP networks for small and medium sized remote branches behind HP-5000



• There are two types of gateways supported namely HP-GW08 and HP-GW128

HP-GW08

HP-GW08 is 8 port analog gateway with comprehensive voice codec support.

Key Features:

- Caller ID
- Flexible dial plans
- Support for 4 modes of fax : T.38, Pass-Through, Modem, Adaptive
- 10/100 Mbps WAN port
- Primary & Secondary SIP Server profile
- LAN ports for local administration
- In-built NAT router.
- Support for advanced telephony features
- QoS for high priority VoIP traffic
- Remotely Manageable and upgradeable via the IP Provision System

DC12V (1)	0 1 2 3 4 8 7 LAND LANS LAND WAN
	Rear View of HP-GW08

Audio Specifications of HP-GW08	Network Specifications of HP-GW08	
• G.711A/U law, G.723.1, G.729AB, iLBC, AMR	• SIP V2.0, SDP, REFER	
Comfortable Noise Generation (CNG)	• RTP/RTCP	
• Voice Activity Detection (VAD)	• STUN, SNTP, DNS, NTP	
• Echo Cancellation (G.168)	• ARP/RARP (RFC 826/903)	
Adaptive Dynamic Jitter Buffer	• DHCP/PPPoE	
• Voice and fax gain control	• TFTP/HTTP/HTTPS	
• DTMF Mode: Signal, RFC2833, INBAND	• VLAN 802.1P/802.1Q	
	Backup Server and Proxy support	
	SNMP support	
	• Diagnostics (debug through Syslog Event Notice)	
	Debug in real time by Telnet	

HP-GW128

HP-GW128 is another cost effective, high density analog extension gateway which can be connected behind HP-5000.

Key Features:

- Cost-effective, High density SIP based Analog (FXS) gateway
- High-quality Voice, Fax and Modem over IP
- Standard 1U cabinet structure
- Scalable from 32 to 128 FXS ports (in multiples of 32 ports)
- Survivability option for subscribes
- Multiple gateways can be stacked together (Physical Stack)
- Comprehensive Quality of Service (QoS) mechanisms
- Multiple voice codec support
- Voice Activity Detection (VAD)
- Comfort Noise Generation (CNG)
- Dynamic adjustment of Jitter Buffer
- Echo cancellation in compliance with ITU-T G.165 / G.168

Note: Multiple HP-GW128s can be stacked together to increase the number of FXS ports more than 128. (Physical Stack)

Protocol	SIP/ RFC3261, SDP / RFC2327, RTP/RTCP, MGCP, H.248	
Voice Coding	G.711A/U, G.723, G.729	
Voice Enhancement	Echo cancellation / Dynamic adjustment of jitter buffer VAD, CNG, lost-packet compensation	
DTMF Transmission Standard	Inband Audio	
	Outband over RTP (RFC2833) / Outband over SIP Info	
Network Characteristics	Static IP, DHCP, PPPoE, 802.1Q VLAN,	
Web configuration management	Configuration Management, supports Tr069	
Network Ports	1 x WAN port, 1 x LAN port (10/100)	
Power Supply	AC power, input at 100~240V, frequency at 48~60Hz	
	DC power, input at 12V	
Power Consumption	<100W (full configuration)	
Maximum Distance	3 Km	

HP-GW128 Specifications



HP-5000

Sailent Feature:

- Call transfer (Blind & Supervised)
- Call back on busy
- Call forward Busy
- Directed Call Pickup
- 3 party Conference
- Silent Monitoring
- Emergency Override & disconnect
- Wake up call
- DID/DOD
- Calling Time restriction
- Hunting group (Linear/Circular)

- Call Hold / Reconnect
- Call forward No answer
- Call forward Unconditional
- Group call pickup
- Do not disturb
- Executive override
- Forced disconnection of call
- Call block selective numbers
- Toll call restriction
- Parallel Ringing
- NTP service

Conference Feature:

- HP-5000 supports an in built conference solution with maximum 64 conference resources. The participants can be internal Analog subscribers, SIP subscribers or external PSTN users.
- There are 2 types of conferences that are supported
- Ad-Hoc conference

Any user in HP-5000 can initiate an Ad-Hoc conference at any time during a call using feature code. User can go on adding additional participants as per need.

• Meet-me conference

Meet-me conference bridge is an in-built functionality of HP-5000 system. A meeting can be established using web based management of HP-5000 with Meeting ID and password.

All the participants can dial in to such conference bridge using these ID and password.

Note: Maximum 64 parties are supported in a Single conference.

- UMR (Unified messaging and recording) system
- HP-5000 supports Voicemail & recording for all members as system features.
- It supports up to 1000 simultaneous lines for Voicemail& voice recording.
- The recordings would be saved in wav format (G711) which supports more than 16000 hours of recording.
- UMR is highly secure and reliable.
- It activates message waiting indication on base SIP phone along with prompt to indicate that there is a voice message for the subscriber.
- Voice Recording also gives statistics about
 - > Calling number
 - Called number
 - Recording time
 - Recording duration
 - Recording channel number
 - UMR allows remote management though LAN & WAN to view, listen, delete, back-up and query of Voice messages and Voice recordings.
- Voicemail would be available to the entire subscriber and each subscriber can access his mailbox via his telephone.
- It is also possible to avail the voicemail on the email of user as an option so that such subscriber can access his voicemail while on the go.

Attendant Console

HP-5000 supports and enhanced operator console which is a PC based application which helps to handle multiple incoming calls from internal subscribers as well as outside callers.

Calls can be handled by a telephone instrument synced with Operator Console GUI based portal.



HP-5000 server specifications

HP-5000 can be installed on industry standard servers only. VMware support is planned for further release. There are three types of deployments

HP-5000 Variants	Small	Medium	Large
CPU	Intel G450 or higher	Intel E3 1230V5 or higher	Intel E5 2630V4 or higher
Memory	8 GB	16 GB	32 GB
Hard Disk capacity	1 TB	1 TB	1 TB

Sales Offices:

Ahmedabad

409, Pinnacle Business Park, Corporate Road, Prahaladnagar, Ahmedabad - 380015 Tel.: +91-79-4040 7500

Chandigarh

C/o Regus Business Centre, SCO 54-56, 3rd Floor, Sector 17A, Chandigarh 160017, India Mob.: +91-99888 99421

Gurgaon

4th floor B-Block, Times Square Building, Sushant Lok Phase 1, Gurgaon – 122001, Haryana Tel.: +91-11-4288 5508

Kolkata

12th Floor, Unit No.3, PS Srijan Corporate Park Tower-1, Plot No. G-2, Block EP & GP, Sector-V, Bidhannagar, Salt Lake Electronics Complex, Kolkata – 700091 Tel.: +91-33-4016 5100

Pune

Office No. 2, 2nd Floor, Patil & ABK House,Pakharbaug Society, Ram Nagar, Bavdhan, Pune, Maharashtra - 411021 Tel.: +91-20-2291 6060

Aurangabad Mob.: +91-77200 25100

Guwahati Mob.: +91-98640 16888

Raipur Mob.: +91-98260 10263

Bengaluru

No. 92-93, 1st Floor, Garden Citi Plaza, Domlur, Koramangala Intermediate Ring Road, Amar Jyothi Layout, Bengaluru - 560071 Tel.: +91-80-4361 8000

Chennai

Unit No.2, West wing, 4th Floor, Maalavika Centre, No.144-145 Kodambakkam High Road, Nungambakkam, Chennai - 600 034 Tel.: +91-44-2833 4190

Hyderabad

H. No. 1-65/2/40 & 41 (P) Plot No: 68, 1st Floor, A1 Towers, Sri Rama Colony, Kavuri Hills Phase 1, Madhapur, Hyderabad – 500 033 Tel.: +91-40-4448 2500

Lucknow

C/O. Regus Infinity Business Hubs, 4th Floor, Halwasiya Court, Hazratganj, Lucknow - 226001, U.P. Mob.: +91-77048 09251

Vadodara

A/413, Atlantis, B/s. Central Square, At Sarabhai Campus, Nr. Genda Circle, Vadodara - 390023 Tel.: +91-265-232 3155

Coimbatore Mob.: +91-90430 02473

Kota Mob.: +91-96549 10792

Ranchi Mob.: +91-76541 90694

Bhopal

2nd Floor, Gomti-Villa, 273, Zone-II, M. P. Nagar, Bhopal - 462011 Tel.: +91-75-5400 4676

Cochin

KG Oxford Business Centre, No 39/4609, 4th Floor C, Sree Kandath Road, Ravipuram, Cochin - 682016 Tel.: +91-484-404 4260

Jaipur 605, 6th Floor, Green House, Ashok Marg, C-Scheme, Jaipur - 302001 Mob.: +91-96549 10792

Mob.: +91-96729 91967

Mumbai

Unit No. 901, 9th Floor, Lodha Supremus, Wing - E, I Think Techno Campus, Kanjurmarg (East), Mumbai - 400 042 Tel.: +91-22-4154 7000

Visakhapatnam

Visakha Business Centre, Cabin S-9, 46-19-5, Manda Vari Street, Behind Big Bazar, Dondaparthy, Visakhapatnam - 530016 Mob.: +91-99493 53919

Dehradun Mob.: +91-95680 10446

Madurai Mob.: +91-90430 02473

Vijayawada Tel.: +91-40-4448 2500

Bhubaneswar

Plot No.382, 2nd Floor Bhoi Nagar, Behind Sahid Nagar Police Station, Bhubaneswar - 751022 Mob.: +91-94370 04318

Delhi

A-25, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044 Tel.: +91-11-4288 5508

Jammu

Lane No-1, R K Vihar Behind, Rama Krishn Ashram, Udhewalla, Bohri, Jammu-180002 Mob.: +91-99888 99421

Mahape

EL - 19, MIDC, TTC Industrial Area, Mahape, Near Nelco, Navi Mumbai - 400710

Nagpur

1st Floor, 6-A, Matruchaya, Modern Society,Chhatrapati Square, Wardha Road, Nagpur - 440015 Tel.: +91-712-3580 369

Goa Mob.: +91-80-4361 8000

Patna Mob.: +91 98713 95569

Trichy Mob.: +91-90430 02473



Corporate Head Office: Unit No. 1001, 10th Floor, Lodha Supremus, Wing - E, I Think Techno Campus, Kanjurmarg (East), Mumbai - 400 042, Maharashtra, India. Tel.: +91-22-4154 7000, Fax: +91-22-4154 7222 Email us - india@progilitytech.com

Contact us: 011-42885508 | www.progilitytech.com